



## ESD SMT Splicing Tape 8mm with Removable PET Backing GSM3708

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: GS
- Model Number: GSM3708
- Minimum Order Quantity: 1 roll
- Price: USD+negotiable+roll
- Packaging Details: 16\*36\*8mm
- Delivery Time: 1-7 days
- Payment Terms: T/T
- Supply Ability: 1+roll+per days



### Product Specification

- Brand Name: GS
- Material: PET
- Model Number: GSM3708
- Dimensions (pc): 14mm X 32mm
- Product Name: Reel Type Splice Tape
- Application: SMT Process
- Customization: Support
- Lead Time: 1-7 Days
- Highlight: **ESD SMT Splicing Tape, PET Backing SMT Splicing Tape, SMT Splicing Tape 8mm**



### More Images



for more products please visit us on [smtmachinepart.com](http://smtmachinepart.com)

## Product Description

### 8mm ESD SMT Splice Tape For Automatic Splicing Machine

#### Product Composition and Design

The GSM3708 splice tape is composed of several key elements that contribute to its effectiveness and ease of use:

1. Adhesive Tapes: The core component that ensures strong bonding between the carrier tapes.
2. Transparent Release Film: Facilitates easy handling and application by protecting the adhesive layer until use.
3. Removable PET Backing: Adds structural integrity and makes the tape easy to manage during the splicing process.

#### Applications

1. Automatic Splicing Machines: The tape is ideal for use with automatic splicing machines, providing high jointing efficiency and ensuring smooth operation without intervention.
2. 4mm Carrier Tapes: While it is highly versatile, the GSM3708 splice tape is especially suited for 4mm carrier tapes.
3. Customization Options: Recognizing the diverse needs of modern manufacturing, the GSM3708 splice tape can be customized to meet specific requirements, ensuring it fits perfectly into any production setup.

#### Instructions for Use

1. Cutting the Carrier Tapes: Use a precision cutting tool to accurately cut the carrier tapes to the desired length. Ensuring clean and precise cuts is crucial for achieving a strong and reliable joint.
2. Preparing the Splice Tape: Carefully remove the release liner from the splice tape to expose the adhesive side. This step is important for ensuring that the adhesive is ready to bond with the carrier tapes.
3. Positioning the Carrier Tapes: Align the ends of the carrier tapes and place them onto the first strip of the splice tape. Accurate alignment is essential for creating a seamless joint that will not disrupt the automated process.
4. Securing the Joint: After positioning the carrier tapes, press the splice tape firmly at various points along the tapes. This ensures a secure and durable bond, capable of withstanding the stresses of the SMT process.

8mm ESD SMT Splice Tape For Automatic Splicing Machine GSM3708 | GSSMT, SMT splice tape, SMT splice tape for pick-and-place, SMT splicing solutions, SMT splice tape types, SMT splice tape price, SMT splice tape suppliers, SMT splice tape yellow, SMT splice tape black, SMT splice tape for feeders, SMT splice tape compatibility, SMT splice tape usage guide, High-quality SMT splice tape, SMT splice tape for Panasonic, SMT splice tape for Fuji, SMT splice tape adhesive, SMT splice tape performance, SMT splice tape advantages, SMT splice tape for high-speed machines, SMT splice tape durability, SMT splice tape best practices



Global Soul Limited



+8613728696610



liyi@gs-smt.com



smtmachinepart.com

Room F3B-016, B Block, Hao Yun Lai Business Building, Liutang road, Bao'an District, Shenzhen, China