

## Dimm Feeder Dual-Track (GS-JAT2110) [Dual-Track]

## **Basic Information**

Place of Origin: ChinaBrand Name: GS

Model Number: GS-JAT2110Minimum Order Quantity: 1/PCS

Price: USD+negotiable+pcs
Packaging Details: 900\*1500\*1650
Delivery Time: 1-3 days
Payment Terms: T/T

Supply Ability: 1+pcs+per days



## **Product Specification**

Model: GS-JAT2110

 Dimensions (length \* Width Please Refer To The Following Drawings \* Height Company Mm):

Mainte

Weight: 330KG
Working Voltage: AC 220V
Air Source Requirements: 0.5-0.7Mpa
Maximum Power: 1300W
Feeding Speed: 2.5s/Pcs

• Operation Panel: Siemens Operation Screen

• Control: Siemens Plc

• Thoroughfare: 2 Channels(The Position Can Be

Customized In The Left And Right Directions)

• Function: The Color Of The Tested Material Can Be

Selected Separately(Default None)

• Adapt To The Material Tray:Please Refer To The Following Drawings

Material: Compatible With PTH And SMT Materials

Dimm Cabinet (GS-JAT2110)[Dual Track]
The DImm tray feeder is a component supply device that installs multiple stacked trays into DIMM slots, arranges them neatly, and sends them out one by one according to the specified time to supply to the plug-in machine.



\*托盘尺寸超出此范围,设备的外形尺寸需要加大。 If the size of the pallet exceeds this range, the external dimensions of the equipment need to be enlarged







If there are special material dimensions, you can contact our company for a solution and customize a dedicated feeder.





+8613728696610



liyi@gs-smt.com



smtmachinepart.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road , Bao'an District , Shenzhen, China