

Customized Horizontal Feeder Model K (GS-AAD2208)

Basic Information

Place of Origin: ChinaBrand Name: GS

Model Number: GS-AAD2208 Minimum Order Quantity: 1 PCS

Price: USD+negotiable+pcs
 Packaging Details: 700*300*300MM
 Delivery Time: 1-7 days

T/T

• Supply Ability: 1+pcs+per days



Product Specification

• Payment Terms:

Model: GS-AAD2208Overall Dimensions (length 570*127*150mm

* Width * Height Unit Mm):

Weight: 14KG
Working Voltage: DC 24V
Maximum Current: 3A
Feeding Speed: 2.5-3s/Pcs
Drive Mode: Pure Electric

• Operation Panel: 0.96-inch TFT Color Screen, 80*160 Pixels

Material Lifting Error: ±0.4mm
 Applicable Tape Width: 63-90 Mm


K Horizontal Feeder (GS-AAD2208)

[Customized Version]

The horizontal feeder is an electronic component supply device that keeps a certain interval and feeds out the horizontal tape-packed electronic components one by one at the prescribed time, shapes them and cuts the lead wires, and supplies them to the insertion machine.



Applicable specifications of woven tape materials:



Code name	Explanation	Reference size (mm)
Α	Tape spacing	5/10
W	Braided tape width	62-90
L	Ontology length	5-22
D	Ontological diameter	3-8
d	Pin diameter	0.4-0.8
g	Pin span	12-26
h	Bending height	7-12
е	Position of Point k	3.5-6.5
f	The distance from the main body to the bending point	>1.5

If there are special material dimensions, you can contact our company for consultation

and to provide solutions and customize exclusive feeders.

GS SMT LTD Global Soul Limited

+8613728696610

liyi@gs-smt.com smtmachinepart.com

 $Room\ F3B-016,\ B\ Block,\ Hao\ Yun\ Lai\ Bussiness\ Building,\ Liutang\ road\ ,\ Bao'an\ District\ ,\ Shenzhen,\ China$